

# M-JPEG IP Cameras

## Features

- 1/3" Interlaced CCD
- Motion Detection
- C or CS mount leons mount
- Automatic Gain Control (AGC)
- Auto Electronic Shutter (AES)
- Auto White Balance (AWB)
- Image quality seloectable at 5different levels for recording
- Image brightness,contrast,saturationand hue adjustable
- Fast ethernet 10/100 base -TX port
- Water marking
- An inbulit microphone
- 340 TV Lines
- Multi-level and multi-user secure manegement
- Firmware update via SD card
- 5V DC / 2A
- Upgrade via SD card



**JCK-31CL**  
M-JPEG Color Lan Camera

## Specification

<b>Model</b>	JCK-31CL
<b>Pick Up Element</b>	1/3" Interlaced CCD
<b>CCD Resolution</b>	NTSC:270k pixels,PAL:320k pixels
<b>Video throughout</b>	Up to 30(25) frame/sec At 352x240(352x288)* Up to 18(15) frame/sec At 720x480(720x576)*
<b>Network throughout</b>	1.5Mbytes/sec
<b>Video Output</b>	1.0 Vpp, 75 ohm,composite,negative
<b>Horizontal Resolution</b>	340 TV lines
<b>Exposure</b>	BLC/AGC/AWB
<b>Electronic Shutter</b>	NTSC: 1/60~ 1/100,000 sec ; PAL: 1/50~ 1/100,000 sec
<b>Sensitivity</b>	0.8 Lux @F=1.2
<b>Auto iris type</b>	DC-iris
<b>Audio</b>	Yes
<b>Microphone</b>	Yes
<b>Compression</b>	M-JPEG
<b>Picture size</b>	4~64 KB
<b>Video fine tune</b>	Brightness,BLC,Saturation,Sharpness
<b>Watermarker</b>	Digital Signature
<b>Network Interface</b>	RJ-45 wired 10/100 Base-TX
<b>Network protocol</b>	TCP/IP, UDP, DHCP, HTTP, SNTP, ICMP,DDNS,DNS
<b>Motion detection</b>	Advanced MD (zone, position, sens)
<b>Secure password / User name</b>	Multi-level / Multi-user
<b>SD socket</b>	Yes
<b>Firmware Upgrade</b>	Upgrade via SD card
<b>Power input</b>	5V DC / 2A
<b>Operating environmental</b>	Require proper environmental housing for outdoor use
<b>Operating temperature</b>	5-50°C (41-122°F )
<b>Regulation</b>	FCC , CE
<b>Dimensions</b>	62(H) x 50(W) x 95(D) mm
<b>Weight</b>	306g

PTZ Speed Domes Network Solutions Dome Cameras Board Cameras Day/Night Cameras Box Cameras

CCTV Equipment, Digital Storage & Network Solutions