


Features

- MPEG-4 ASP Compression
- Up to Full D1 resolution
- 30/25 fps Frame Rate
- Dual MPEG-4 Video Stream Output
- LAN and WAN Port Built-in
- Supports TCP/IP, UDP, HTTP, DHCP, RTP, RTSP, PPPoE, FTP & SMTP.
- QoS enabled (L3) Video Streaming
- Digital Time Code Embedded
- Motion detection
- Isolated DI/DO Supported
- RoHS Compliant
- Application Software:
Supports Windows 2000/Win XP OS
Supports Up to 16 IP Cameras
Supports PTZ Control
Supports Motion Detection
Supports DI/DO



WVS-120

Wall-mount Type MPEG-4 Video Server

WVS-120A

Wall-mount Type MPEG-4 Video Server + 2-Way Audio

Specification

Model	WVS-120	WVS-120A
Image Compression	MPEG-4 ASP Compliant Compression	
Image Frame Rate	NTSC: 30 fps@720 x 480 PAL :25 fps@720 x 576	NTSC: 30 fps@352 x 240 PAL: 25 fps@352 x 288
Max. Resolution	Full D1	
LAN/WAN Port	10/100 Base-T for LAN and WAN	
Support Protocols	TCP, UDP, IP, HTTP, DHCP, PPPoE ,RTP,RTSP,FTP,SMTP	
Bit Rate	28 K ~ 3 M bps	
Network	Ethernet (10/100Base-T), RJ-45 connector	
Composite Input	CVBS, 1.0Vp-p with 75 Ohm, BNC connector	
Composite Output	CVBS, 1.0Vp-p with 75 Ohm, BNC connector	
Multi-stream	Up to 4 Configurable Frame Rate/Bit Rate Streams for Preview and Recording	
Serial Port	RS-485 Half Duplex (Terminal Block); RS-422/RS-232 Full Duplex (Terminal Block)	
Audio	—	2 Way
Alarm I/O	2, TTL, Terminal Block	
Web Browser	Microsoft Internet Explorer 6.0 or above	
SDK	ActiveX Control, C SDK	
Security	Password Protection : Configured By the Administrator	
Operating Temperature	+5° ~ 50° C (40 ~ 122 °F)	
Power Consumption	Max. 7.5 W	
Power Supply	DC 12 V ±10%	
Dimension	112 mm(W) x 37.2 mm(H) x 119 mm(D)	
Weight	350 Grams	

Dimensions

