


MPEG-4 Video Server

Features

- MPEG-4 ASP Compression
- 2 x Video Inputs / 2 x Video Outputs
- Up to Full D1 resolution
- 30/25 fps Frame Rate/Channel
- Dual MPEG-4 Video Stream Output
- LAN and WAN Port Built-in
- Supports TCP/IP, UDP, HTTP, DHCP, RTP, RTSP, PPPoE, FTP & SMTP.
- QoS enabled (L3) Video Streaming
- Digital Time Code Embedded
- Motion detection
- Isolated DI/DO Supported
- Application Software:
Supports Windows 2000/Win XP OS
Supports Up to 16 IP Cameras
Supports PTZ Control
Supports Motion Detection
Supports DI/DO



WVS-220

2-Channel MPEG-4 Video Server with Full D1 Resolution

WVS-220A

2-Channel MPEG-4 Video Server with Full D1 Resolution + 2-Way Audio

Specification

Model	WVS-220	WVS-220A
Image Compression	MPEG-4 ASP Compliant Compression	
Image Frame Rate	NTSC: 30 fps/PAL: 25 fps @Full D1 Resolution	
Max. Resolution	Full D1(NTSC: 720 x 480 / PAL: 720 x 576) per channel CIF (NTSC: 352 x 240 / PAL: 352 x 288) per channel QCIF (NTSC: 160 x 112 / PAL: 176 x 144) per channel	
LAN/WAN Port	10/100 Base-T for LAN and WAN	
Support Protocols	TCP, UDP, IP, HTTP, DHCP, PPPoE, RTP, RTSP, FTP, SMTP	
Bit Rate	28 K ~ 3 M bps	
Network	Ethernet (10/100Base-T), RJ-45 connector	
Composite Input	2, CVBS, 1.0Vp-p with 75 Ohm, BNC connector	
Composite Output	2, CVBS, 1.0Vp-p with 75 Ohm, BNC connector	
Multi-stream	Up to 4 Configurable Frame Rate/Bit Rate Streams for Preview and Recording	
Serial Port	RS-485 Half Duplex (Terminal Block); RS-422/RS-232 Full Duplex (Terminal Block)	
Audio Compression	---	8 kHz, Mono, PCM
Audio Line Input/Output	---	Unbalanced, 1.4Vp-p, 1Vrms, 3.5 mm jack
Alarm I/O	2, TTL, Terminal Block	
Web Browser	Microsoft Internet Explorer 6.0 or above	
SDK	ActiveX Control, C SDK	
Security	Password Protection : Configured By the Administrator	
Operating Temperature	5 ~ 50 °C (40 ~ 122 °F)	
Power Consumption	Max. 7.5 W	
Power Supply	DC 12 V ±10%	
Dimension	139 mm(W) x 44.2 mm(H) x 144 mm(D)	
Weight	570 Grams	

Dimensions

