

# SRD-870/870D

8CH H.264 Digital Video Recorder



## Features

- 8ch 4CIF real-time DVR
- Video (H.264) / Audio (ADPCM)
- Up to 240 (NTSC) / 200 (PAL)ips recording rate
- Up to 8ch audio inputs and 1ch audio outputs
- Combined BNC and VGA/HDMI video output for main display
- SRD-870 : Max 6 internal HDD (HDD x 6)  
SRD-870D : Max 5 internal HDD (HDD x 5)
- HDD & DVD SATA interface
- DDNS
- Built-in web viewer
- DVD-RW (SRD-870D)
- Event notifications by E-mail

## Technical Specifications

	SRD-870	SRD-870D
<b>DISPLAY</b>		
Video	Inputs	8 Composite video 0.5-1Vpp, 75 ohm automatic termination
	Resolution	NTSC : 704 x 480 / PAL : 704 x 576
	Frame Rate	NTSC : 240ips / PAL : 200ips
Live	Resolution	NTSC : 704 x 480 / PAL : 704 x 576
	Multi Screen Display	1 / 4 / 6 / 8 / 9 / 13 / PIP
<b>PERFORMANCE</b>		
Operating System	Embedded	Linux
	Compression	H.264
Recording	Record Rate	NTSC : Up to 240ips@704 x 480 / PAL : Up to 200ips@704 x 576 NTSC : Up to 240ips@704 x 240 / PAL : Up to 200ips@704 x 288 NTSC : Up to 240ips@352 x 240 / PAL : Up to 200ips@352 x 288
	Mode	NTSC : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (0.9 / 1.9 / 3.8 / 7.5 / 15 / 30ips) PAL : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (0.8 / 1.6 / 3.1 / 6.2 / 12.5 / 25ips)
	Overwrite Modes	Continuous Up to 30sec. (5, 10, 20, 30sec.)
Search & Playback	Pre-alarm	Up to 6hour. (5, 10, 20, 30sec, 1, 3, 5, 10, 2min, 1, 2, 3, 4, 5, 6hour)
	Post-alarm	Up to 6hour. (5, 10, 20, 30sec, 1, 3, 5, 10, 2min, 1, 2, 3, 4, 5, 6hour)
	Search Mode	Date/Time, Event, Back up, Pos, Motion (*All searching mode include preview function)
Network	Playback Function	Fast forward / backward, Slow forward / backward, Step forward / backward
	Transmission Speed	Up to 15Mbps, Unlimited 4M / 2 / 1.5 / 1 Mbps / 800 / 600 / 500 / 400 / 300 / 200 / 100 / 50 kbps
	Bandwidth Control	Automatic
Storage	Multi Stream	H.264 (4CIF / 2CIF / CIF)
	Max. Remote Users	Search 3 / Live unicast 10 / Live multicast 20
	Protocol Support	TCP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, DDNS, RTP, RTSP
	Monitoring	Net-i viewer, Smart viewer, Web viewer
Security	Internal HDD	Up to 6 SATA HDDs
	External HDD	Up to 2 expansion bay (up to 4 HDD each)
	DVD Writer (Back up)	N/A
INTERFACE	USB (Back up)	Up to 2 expansion bay (up to 4 HDD each)
	File Format (Back up)	AVI, MDB (DVR play back), EXE (include player)
	Password Protection	1 Admin, 10 Group, 20 User per 1 Group, User can be assigned authority for function
Monitors	Data Authentication	Watermark
	VGA	Analog RGB 800 x 600, 1024 x 768, 1280 x 1024 resolution
	HDMI	480p / 720p / 1080p resolution
Audio	Main Composite	BNC, 1 Vp-p, 75 ohm
	Spot Composite	1 BNC, 1 Vp-p, 75 ohm, Support multi screen and camera title
	Loop Outputs	8
Alarm	Inputs	8 Line in (Built in 4ch, Option : audio extension cable)
	Output	1 Line
	Compression	ADPCM
Connections	Sampling Rate	16KHz
	Inputs	Terminal 8 inputs, NO/NC
	Outputs	Terminal 4 relay outputs, NO/NC
General	Remote Notification	Notification via e-mail
	Ethernet	1 RJ-45 10/100/1000 Base-T
	Serial Interface	RS-232
Electrical	PTZ Control Interface	RS-485
	PTZ Keyboard	RS-485
	USB	USB 2.0, 3 ports
Environmental	eSATA	2 External SATA ports
	Application Support	Mouse, Remote controller
	Supported	Samsung-E, Samsung-T, Pelco-D, Pelco-P, Panasonic, Philips, AD
Mechanical	Protocols	DIAMOND, ERNA, KALATEL, VCLTP, VICON
	Dimensions (WxHxD)	440 x 88 x 430mm (17.32" x 3.46" x 16.93")
	Weight (2x Hard Disks)	Approx. 7.5Kg (16.53 lb)
Language	Rack Mount Kit	2ea
		English, Korean, Spanish, French, German, Italian, Portuguese, Polish, Russian, Turkish, Japanese, Czech, Swedish, Danish, Chinese, Netherlands

## Dimensions

Unit : mm (inch)

